400G QSFP-DD TO 400G QSFP-DD ACC

KEY FEATURES

- Support 400G QSFP-DD to 400G QSFP-DD
- Support 8x53.125G PAM4
- IEEE 802.3cd
- QSFP-DD/ QSFP56 MSA
- **Temperature Range: 0°C - 70°C**
- **Max. Power Consumption:<1.5W each end**
- 3.3V Power Supply
- **Made in Thailand**
- RoHS Compliance

SANWA P/N	Length	AWG
400 QDACC-030	3.0m	30AWG
400 QDACC-050	5.0m	28AWG
400 GDACC-060	6.0m	28AWG

APPLICATIONS

- Switches, Servers and Storage Devices
- Data Center Networks
- High Performance Computing

400G QSFP112 TO 400G QSFP112 ACC

KEY FEATURES

- Support 4x106.25G PAM4
- QSFP112 MSA
- IEEE 802.3ck
- **Temperature Range: 0°C - 70°C**
- **Max. Power Consumption:<1.0W each end**
- 3.3V Power Supply
- **Made in Thailand**
- Cable: PVC Black
- RoHS Compliance

SANWA P/N	Length	AWG
400 Q112ACC-030	3.0m	30AWG
400 Q112ACC-035	3.5m	28AWG
400 Q112ACC-050	5.0m	26AWG

APPLICATIONS

- Switches, Servers and Storage Devices
- Data Center Networks
- High Performance Computing

SANWA Technologies, Inc. www.sanwa-tech.com sales@snwtech.com

Americas Sales-TX
4012 Preston Rd.
Plano, TX 75093
Tel: +1 (972)-503-3031
Fax: +1 (972)-503-3032

Americas Sales-MA
287 Turnpike Road
Westborough, MA 01581
Tel: +1(508)-616-9500
Fax: +1(508)-616-9600

Europe Sales
Aleja Armii Krajowej 61, Bud. C,
50-541 Wrocław, PL
Tel: +48 71 7277237
Fax: :+48 71 7939911

Asia Sales
13F, Changxing Rd., Luzhou Dist.,
New Taipei City 247, Taiwan
(R.O.C.)
Tel: +886 939512000
Fax: +886 2 8285450